

EECS 10: Computational Methods in Electrical and Computer Engineering

Lecture 18

Rainer Dömer

doemer@uci.edu

The Henry Samueli School of Engineering
Electrical Engineering and Computer Science
University of California, Irvine

Lecture 18: Overview

- Character Arrays: Strings
 - Input and output
 - ASCII table
 - Example: Sort strings alphabetically
 - Task
 - Approach
 - Algorithm *Bubble Sort*
 - Program `Bubblesort.c`

Character Arrays: Strings

- Character Arrays: *Strings*
 - Strings are null-terminated arrays of characters
 - String output
 - `printf()` conversion: "%s"
- Example:

```
char s1[] = {'H','e','l','l','o',0};

printf("s1 is %s.\n", s1);
```

s1 is Hello.

s1	
0	'H'
1	'e'
2	'l'
3	'l'
4	'o'
5	0

EECS10: Computational Methods in ECE, Lecture 18

(c) 2004 R. Doemer

3

Character Arrays: Strings

- Character Arrays: *Strings*
 - Strings are null-terminated arrays of characters
 - String output
 - `printf()` conversion: "%s"
- Example:

```
char s1[] = {'H','e','l','l','o',0};
char s2[] = "Hello";

printf("s1 is %s.\n", s1);
printf("s2 is %s.\n", s2);
```

s1 is Hello.
s2 is Hello.

s2	
0	'H'
1	'e'
2	'l'
3	'l'
4	'o'
5	0

EECS10: Computational Methods in ECE, Lecture 18

(c) 2004 R. Doemer

4

Character Arrays: Strings

- Character Arrays: *Strings*
 - Strings are null-terminated arrays of characters
 - String output
 - `printf()` conversion: "%s"
- Example:

```
char s1[] = {'H','e','l','l','o',0};
char s2[] = "Hello";
printf("s1 is %s.\n", s1);
printf("s2 is %s.\n", s2);
s1[1] = 'i';
s1[2] = 0;
printf("Modified s1 is %s.\n", s1);
```

s1 is Hello.
s2 is Hello.
Modified s1 is Hi.

s2	
0	'H'
1	'i'
2	0
3	'l'
4	'o'
5	0

EECS10: Computational Methods in ECE, Lecture 18

(c) 2004 R. Doemer

5

Character Arrays: Strings

- Character Arrays: *Strings*
 - Strings are null-terminated arrays of characters
 - String input
 - `scanf()` conversion: "%Ns",
 where N specifies maximum field width = array size - 1
 - address argument can be `&string[0]`
- Example:

```
char s1[6];
printf("Enter a string: ");
scanf("%s", &s1[0]);
printf("s1 is %s.\n", s1);
```

Enter a string: Test
s1 is Test.

s1	
0	'T'
1	'e'
2	's'
3	't'
4	0
5	0

EECS10: Computational Methods in ECE, Lecture 18

(c) 2004 R. Doemer

6

Character Arrays: Strings

- Character Arrays: *Strings*
 - Strings are null-terminated arrays of characters
 - String input
 - `scanf()` conversion: "%Ns", where **N** specifies maximum field width = array size - 1
 - address argument can be `&string[0]` or simply `string`

- Example:

```
char s1[6];
printf("Enter a string: ");
scanf("%5s", s1);
printf("s1 is %s.\n", s1);
```

Enter a string: EECS
s1 is EECS.

s1	
0	'E'
1	'E'
2	'C'
3	'S'
4	0
5	0

Character Arrays: Strings

- Character Arrays: *Strings*
 - Strings are null-terminated arrays of characters
 - Characters are represented by numeric values
 - ASCII table defines character values 0-127
- Example:

```
char s1[] = "ABC12";
int i = 0;

while(s1[i])
{ printf("%c = %d\n",s1[i],s1[i]);
  i++; }
```

A = 65
B = 66
C = 67
1 = 49
2 = 50

s1	
0	'A'
1	'B'
2	'C'
3	'1'
4	'2'
5	0

Character Arrays: Strings

- ASCII Table
 - American Standard Code for Information Interchange

0 <i>NUL</i>	1 <i>SOH</i>	2 <i>STX</i>	3 <i>ETX</i>	4 <i>EOT</i>	5 <i>ENQ</i>	6 <i>ACK</i>	7 <i>BEL</i>
8 <i>BS</i>	9 <i>HT</i>	10 <i>NL</i>	11 <i>VT</i>	12 <i>NP</i>	13 <i>CR</i>	14 <i>SO</i>	15 <i>SI</i>
16 <i>DLE</i>	17 <i>DC1</i>	18 <i>DC2</i>	19 <i>DC3</i>	20 <i>DC4</i>	21 <i>NAK</i>	22 <i>SYN</i>	23 <i>ETB</i>
24 <i>CAN</i>	25 <i>EM</i>	26 <i>SUB</i>	27 <i>ESC</i>	28 <i>FS</i>	29 <i>GS</i>	30 <i>RS</i>	31 <i>US</i>
32 <i> </i>	33 <i>!</i>	34 <i>"</i>	35 <i>#</i>	36 <i>\$</i>	37 <i>%</i>	38 <i>&</i>	39 <i>'</i>
40 <i>(</i>	41 <i>)</i>	42 <i>*</i>	43 <i>+</i>	44 <i>,</i>	45 <i>-</i>	46 <i>.</i>	47 <i>/</i>
48 <i>0</i>	49 <i>1</i>	50 <i>2</i>	51 <i>3</i>	52 <i>4</i>	53 <i>5</i>	54 <i>6</i>	55 <i>7</i>
56 <i>8</i>	57 <i>9</i>	58 <i>:</i>	59 <i>;</i>	60 <i><</i>	61 <i>=</i>	62 <i>></i>	63 <i>?</i>
64 <i>@</i>	65 <i>A</i>	66 <i>B</i>	67 <i>C</i>	68 <i>D</i>	69 <i>E</i>	70 <i>F</i>	71 <i>G</i>
72 <i>H</i>	73 <i>I</i>	74 <i>J</i>	75 <i>K</i>	76 <i>L</i>	77 <i>M</i>	78 <i>N</i>	79 <i>O</i>
80 <i>P</i>	81 <i>Q</i>	82 <i>R</i>	83 <i>S</i>	84 <i>T</i>	85 <i>U</i>	86 <i>V</i>	87 <i>W</i>
88 <i>X</i>	89 <i>Y</i>	90 <i>Z</i>	91 <i>[</i>	92 <i>\</i>	93 <i>]</i>	94 <i>^</i>	95 <i>_</i>
96 <i>`</i>	97 <i>a</i>	98 <i>b</i>	99 <i>c</i>	100 <i>d</i>	101 <i>e</i>	102 <i>f</i>	103 <i>g</i>
104 <i>h</i>	105 <i>i</i>	106 <i>j</i>	107 <i>k</i>	108 <i>l</i>	109 <i>m</i>	110 <i>n</i>	111 <i>o</i>
112 <i>p</i>	113 <i>q</i>	114 <i>r</i>	115 <i>s</i>	116 <i>t</i>	117 <i>u</i>	118 <i>v</i>	119 <i>w</i>
120 <i>x</i>	121 <i>y</i>	122 <i>z</i>	123 <i>{</i>	124 <i> </i>	125 <i>}</i>	126 <i>~</i>	127 <i>DEL</i>

EECS10: Computational Methods in ECE, Lecture 18

(c) 2004 R. Doemer

9

Character Arrays: Strings

- Case Study: *Bubble Sort*
 - Task: Sort an array of strings alphabetically
 - Input: Array of 10 strings entered by the user
 - Output: Array of 10 strings in alphabetical order
- Approach: Divide and Conquer
 - Step 1: Let user enter 10 strings
 - Step 2: Sort the array of strings
 - Step 3: Output the strings in order

EECS10: Computational Methods in ECE, Lecture 18

(c) 2004 R. Doemer

10

Character Arrays: Strings

- Case Study: *Bubble Sort*
 - Task: Sort an array of strings alphabetically
 - Input: Array of 10 strings entered by the user
 - Output: Array of 10 strings in alphabetical order
- Approach: Divide and Conquer
 - Step 1: Let user enter 10 strings
 - Step 2: Sort the array of strings
 - Algorithm
 - compare all possible pairs of strings and swap the pair if they are not in alphabetical order
 - String comparison
 - compare character pairs alphabetically: use ASCII table!
 - String swap (exchange two strings in place)
 - swap each character pair in the two strings
 - Step 3: Output the strings in order

EECS10: Computational Methods in ECE, Lecture 18

(c) 2004 R. Doemer

11

Character Arrays: Strings

- Program example: **BubbleSort.c** (part 1/7)

```
/*
 * BubbleSort.c: sort strings alphabetically
 * author: Rainer Doemer
 */
/*
 * modifications:
 */
/* 11/06/04 RD initial version */

#include <stdio.h>

/* constant definitions */
#define NUM 10 /* ten strings */
#define LEN 20 /* of length 20 */

/* function declarations */

void EnterText(char Text[NUM][LEN]);
void PrintText(char Text[NUM][LEN]);
int CompareStrings(char s1[LEN], char s2[LEN]);
void SwapStrings(char s1[LEN], char s2[LEN]);
void BubbleSort(char Text[NUM][LEN]);
...
```

EECS10: Computational Methods in ECE, Lecture 18

(c) 2004 R. Doemer

12

Character Arrays: Strings

- Program example: **BubbleSort.c** (part 2/7)

```
...
/* function definitions */

/* let the user enter the text array */

void EnterText(char Text[NUM][LEN])
{
    int i;

    for(i = 0; i < NUM; i++)
        { printf("Enter text string %2d: ", i+1);
          scanf("%19s", Text[i]);
        } /* rof */
} /* end of EnterText */

...
```

Character Arrays: Strings

- Program example: **BubbleSort.c** (part 3/7)

```
...
/* print the text array on the screen */

void PrintText(char Text[NUM][LEN])
{
    int i;

    for(i = 0; i < NUM; i++)
        { printf("String %2d: %s\n", i+1, Text[i]);
        } /* rof */
} /* end of PrintText */

...
```

Character Arrays: Strings

- Program example: **BubbleSort.c** (part 4/7)

```
...
/* alphabetically compare strings s1 and s2:      */
/* return -1, if string s1 < string s2           */
/* return  0, if string s1 = string s2           */
/* return  1, if string s1 > string s2           */

int CompareStrings(char s1[LEN], char s2[LEN])
{
    int i;

    for(i = 0; i < LEN; i++)
        { if (s1[i] > s2[i])
            { return(1); }
            if (s1[i] < s2[i])
            { return(-1); }
            if (s1[i] == 0 || s2[i] == 0)
            { break; }
        } /* rof */
    return 0;
} /* end of CompareStrings */
...
```

Character Arrays: Strings

- Program example: **BubbleSort.c** (part 5/7)

```
...
/* swap/exchange the strings s1 and s2 in place */

void SwapStrings(char s1[LEN], char s2[LEN])
{
    int i;
    char c;

    for(i = 0; i < LEN; i++)
        { c = s1[i];
          s1[i] = s2[i];
          s2[i] = c;
        } /* rof */
} /* end of SwapStrings */

...
```

Character Arrays: Strings

- Program example: **BubbleSort.c** (part 6/7)

```

...
/* sort the text array by comparing every pair */
/* of strings; if the pair of strings is not in */
/* alphabetical order, swap it */

void BubbleSort(char Text[NUM][LEN])
{
    int i, j;

    for(i = 0; i < NUM-1; i++)
        { for(j = i+1; j < NUM; j++)
            { if (CompareStrings(Text[i], Text[j]) > 0)
                { SwapStrings(Text[i], Text[j]);
                } /* fi */
            } /* rof */
        } /* end of BubbleSort */
}

...

```

EECS10: Computational Methods in ECE, Lecture 18

(c) 2004 R. Doemer

17

Character Arrays: Strings

- Program example: **BubbleSort.c** (part 7/7)

```

...
/* main function: enter, sort, print the text */
int main(void)
{
    /* local variables */
    char Text[NUM][LEN]; /* NUM strings, length LEN */

    /* input section */
    EnterText(Text);

    /* computation section */
    BubbleSort(Text);

    /* output section */
    PrintText(Text);

    /* exit */
    return 0;
} /* end of main */

/* EOF */

```

EECS10: Computational Methods in ECE, Lecture 18

(c) 2004 R. Doemer

18

Character Arrays: Strings

- Example session: **BubbleSort.c**

```
% vi BubbleSort.c
% gcc BubbleSort.c -o BubbleSort -Wall -ansi
% BubbleSort
Enter text string 1: Charlie
Enter text string 2: William
Enter text string 3: Donald
Enter text string 4: John
Enter text string 5: Jane
Enter text string 6: Jessie
Enter text string 7: Donald
Enter text string 8: Henry
Enter text string 9: George
Enter text string 10: Emily
String 1: Charlie
String 2: Donald
String 3: Donald
String 4: Emily
String 5: George
String 6: Henry
String 7: Jane
String 8: Jessie
String 9: John
String 10: William
%
EE%
```