

EECS 10: Computational Methods in Electrical and Computer Engineering

Lecture 13

Rainer Dömer

doemer@uci.edu

The Henry Samueli School of Engineering
Electrical Engineering and Computer Science
University of California, Irvine

Lecture 13: Overview

- Functions
 - Introduction to Function Concepts
 - Function Declaration
 - Function Definition
 - Function Call
 - Example `Square.c`
 - Example `Cylinder.c`

Functions

- Introduction to Functions
 - Important programming concepts
 - Hierarchy
 - Encapsulation
 - Information hiding
 - Divide and conquer
 - Software reuse
 - Don't re-invent the wheel!
 - Program composition
 - C program = Set of functions
 - starting point: function named `main`
 - Libraries = Set of functions
 - predefined functions (possibly written by somebody else)

Functions

- C programming language distinguishes 3 constructs
 - Function declaration
 - declaration of function name, parameters, and return type
 - Function definition
 - extension of a function declaration with a function body
 - definition of the function behavior
 - Function call
 - invocation of a function

Functions

- Function declaration
 - aka. function prototype or function signature
 - declares
 - function name
 - function parameters
 - type of return value
- Example:

```
double Square(double a);
```

 - function is named **Square**
 - function takes one parameter **a** of type **double**
 - function returns a value of type **double**

Functions

- Function definition
 - extends a function declaration with a function body
 - defines the statements executed by the function
 - may use local variables for the computation
 - returns result value via **return** statement (if any)
- Example:

```
double Square(double a)
{
    double r;
    r = a * a;
    return r;
}
```

Functions

- Function call
 - expression invoking a function
 - supplies arguments for formal parameters
 - invokes the function
 - result is the value returned by the function
- Example:

```
double x, y;  
y = Square(x);
```

- function **Square** is called
- argument **x** is passed for parameter **a** (by value)
- value returned by the function is assigned to **y**

Functions

- C programming language distinguishes 3 constructs
 - Function declaration
 - declaration of function name, parameters, and return type
 - Function definition
 - extension of a function declaration with a function body
 - definition of the function behavior
 - Function call
 - invocation of a function
- C program rules
 - A function must be declared before it can be called.
 - Multiple function declarations are allowed (if they match).
 - A function definition is an implicit function declaration.
 - A function must be defined exactly once in a program.
 - A function may be called any number of times.

Functions

- Program example: **Square.c** (part 1/2)

```
/* Square.c: example demonstrating functions */
/*
 * author: Rainer Doemer
 */
/* modifications:
 * 10/27/04 RD initial version
 */

#include <stdio.h>

/* function declaration */

double square(double a);

/* function definition */

double square(double a)
{
    return a * a;
} /* end of square */

...
```

Functions

- Program example: **Square.c** (part 2/2)

```
...
/* main function */

int main(void)
{ /* variable definitions */
    double x, y;

    /* input section */
    printf("Please enter a value for x: ");
    scanf("%lf", &x);

    /* computation section */
    y = square(x);

    /* output section */
    printf("The square of %g is %g\n", x, y);

    /* exit */
    return 0;
} /* end of main */

/* EOF */
```

Functions

- Example session: **Square.c**

```
% vi Square.c
% gcc Square.c -o Square -Wall -ansi
% Square
Please enter a value for x: 3
The square of 3 is 9
% Square
Please enter a value for x: 5.5
The square of 5.5 is 30.25
%
```

Functions

- Program example: **Cylinder.c** (part 1/3)

```
/* Cylinder.c: cylinder functions          */
/* author: Rainer Doemer                   */
/* modifications:                          */
/* 10/25/05 RD  initial version         */

#include <stdio.h>

/* cylinder functions */

double pi(void)
{
    return(3.1415927);
}

double CircleArea(double r)
{
    return(pi() * r * r);
}
...
```

Functions

- Program example: **Cylinder.c** (part 2/3)

```
...
double CirclePerimeter(double r)
{
    return(2 * pi() * r);
}

double Surface(double r, double h)
{
    double side, lid;
    side = CirclePerimeter(r) * h;
    lid = CircleArea(r);
    return(side + 2*lid);
}

double Volume(double r, double h)
{
    return(CircleArea(r) * h);
}
...
```

EECS10: Computational Methods in ECE, Lecture 13

(c) 2006 R. Doemer

13

Functions

- Program example: **Cylinder.c** (part 3/3)

```
...
/* main function */
int main(void)
{
    double r, h, s, v;

    /* input section */
    printf("Please enter the radius: ");
    scanf("%lf", &r);
    printf("Please enter the height: ");
    scanf("%lf", &h);

    /* computation section */
    s = Surface(r, h);
    v = Volume(r, h);

    /* output section */
    printf("The surface area is %f.\n", s);
    printf("The volume is %f.\n", v);

    return 0;
} /* end of main */
```

EECS10: Computational Methods in ECE, Lecture 13

(c) 2006 R. Doemer

14

Functions

- Example session: `Cylinder.c`

```
% vi Cylinder.c
% gcc Cylinder.c -o Cylinder -Wall -ansi
% Cylinder
Please enter the radius: 5.0
Please enter the height: 8.0
The surface area is 408.407051.
The volume is 628.318540.
%
```