

EECS 10: Computational Methods in Electrical and Computer Engineering

Lecture 15

Rainer Dömer

doemer@uci.edu

The Henry Samueli School of Engineering
Electrical Engineering and Computer Science
University of California, Irvine

Lecture 15: Overview

- Course administration
 - Reminder: Midterm course evaluation
- Functions
 - Terms and concepts
 - Scope rules
 - Scope example
- Debugging
 - Stack frames

Course Administration

- Midterm Course Evaluation
 - Open until tonight, 8pm!
 - Oct. 31, 2007, 8am - Nov. 5, 2007, 8pm
 - Online via EEE Evaluation application
- Feedback from students to instructors
 - Completely voluntary
 - Completely anonymous
 - Very valuable
 - Help to improve this class!
- Mandatory Final Course Evaluation
 - expected for week 10 (TBA)

Functions

- Review: Terms and Concepts
 - Function declaration
 - function prototype with name, parameters, and return type
 - Function parameters
 - formal parameters holding the data supplied to a function
 - Function definition
 - extended declaration, defines the behavior in function body
 - Local variables
 - variables defined locally in a function body
 - Function call
 - expression invoking a function with supplied arguments
 - Function arguments
 - arguments passed to a function call (initial values for parameters)
 - Return value
 - result computed by a function call

Functions

- Scope of an identifier
 - Portion of the program where the identifier can be referenced
 - aka. accessibility, visibility
- Scope rules
 - Global variables: *file scope*
 - Declaration outside any function (at global level)
 - Scope in entire source file after declaration
 - Function parameters: *function scope*
 - Declaration in function parameter list
 - Scope limited to this function body (entirely)
 - Local variables: *block scope*
 - Declaration inside a compound statement (i.e. function body)
 - Scope limited to this compound statement block (entirely)

Scope Rules: Example

```
#include <stdio.h>
int square(int a);
int add_y(int x);
int x = 5,
    y = 7;
int square(int a)
{
    int s;
    s = a * a;
    return s;
}
int add_y(int x)
{
    int s;
    s = x + y;
    return s;
}
int main(void)
{
    int z;
    z = square(x);
    z = add_y(z);
    printf("%d\n", z);
    return 0;
}
```

Header file inclusion

Function declarations

Global variables

Function definition
Local variableFunction definition
Local variableFunction definition
Local variable

Scope Rules: Example

```
#include <stdio.h>
int square(int a);
int add_y(int x);

int x = 5,
    y = 7;
int square(int a)
{
    int s;
    s = a * a;
    return s;
}
int add_y(int x)
{
    int s;
    s = x + y;
    return s;
}
int main(void)
{
    int z;
    z = square(x);
    z = add_y(z);
    printf("%d\n", z);
    return 0;
}
```

Scope of global functions
`printf()`, `scanf()`, etc.

EECS10: Computational Methods in ECE, Lecture 15

(c) 2007 R. Doemer

7

Scope Rules: Example

```
#include <stdio.h>
int square(int a);
int add_y(int x);

int x = 5,
    y = 7;
int square(int a)
{
    int s;
    s = a * a;
    return s;
}
int add_y(int x)
{
    int s;
    s = x + y;
    return s;
}
int main(void)
{
    int z;
    z = square(x);
    z = add_y(z);
    printf("%d\n", z);
    return 0;
}
```

Scope of global function
`square()`

EECS10: Computational Methods in ECE, Lecture 15

(c) 2007 R. Doemer

8

Scope Rules: Example

```
#include <stdio.h>
int square(int a);
int add_y(int x);

int x = 5,
    y = 7;
int square(int a)
{
    int s;
    s = a * a;
    return s;
}
int add_y(int x)
{
    int s;
    s = x + y;
    return s;
}
int main(void)
{
    int z;
    z = square(x);
    z = add_y(z);
    printf("%d\n", z);
    return 0;
}
```

Scope of global function
add_y()

Scope Rules: Example

```
#include <stdio.h>
int square(int a);
int add_y(int x);
int x = 5,
    y = 7;
int square(int a)
{
    int s;
    s = a * a;
    return s;
}
int add_y(int x)
{
    int s;
    s = x + y;
    return s;
}
int main(void)
{
    int z;
    z = square(x);
    z = add_y(z);
    printf("%d\n", z);
    return 0;
}
```

Scope of global variable
x

Scope Rules: Example

```
#include <stdio.h>
int square(int a);
int add_y(int x);
int x = 5,
     y = 7;
int square(int a)
{
    int s;
    s = a * a;
    return s;
}
int add_y(int x)
{
    int s;
    s = x + y;
    return s;
}
int main(void)
{
    int z;
    z = square(x);
    z = add_y(z);
    printf("%d\n", z);
    return 0;
}
```

Scope of global variable
y

EECS10: Computational Methods in ECE, Lecture 15

(c) 2007 R. Doemer

11

Scope Rules: Example

```
#include <stdio.h>
int square(int a);
int add_y(int x);
int x = 5,
     y = 7;
int square(int a)
{
    int s;
    s = a * a;
    return s;
}
int add_y(int x)
{
    int s;
    s = x + y;
    return s;
}
int main(void)
{
    int z;
    z = square(x);
    z = add_y(z);
    printf("%d\n", z);
    return 0;
}
```

Scope of parameter
a

EECS10: Computational Methods in ECE, Lecture 15

(c) 2007 R. Doemer

12

Scope Rules: Example

```
#include <stdio.h>
int square(int a);
int add_y(int x);
int x = 5,
     y = 7;
int square(int a)
{
    int s;
    s = a * a;
    return s;
}
int add_y(int x)
{
    int s;
    s = x + y;
    return s;
}
int main(void)
{
    int z;
    z = square(x);
    z = add_y(z);
    printf("%d\n", z);
    return 0;
}
```

Scope of local variable
s

EECS10: Computational Methods in ECE, Lecture 15

(c) 2007 R. Doemer

13

Scope Rules: Example

```
#include <stdio.h>
int square(int a);
int add_y(int x);
int x = 5,
     y = 7;
int square(int a)
{
    int s;
    s = a * a;
    return s;
}
int add_y(int x)
{
    int s;
    s = x + y;
    return s;
}
int main(void)
{
    int z;
    z = square(x);
    z = add_y(z);
    printf("%d\n", z);
    return 0;
}
```

*Local variables
are independent!*
(unless their scopes are nested)

Scope of local variable
s

Scope of local variable
s

EECS10: Computational Methods in ECE, Lecture 15

(c) 2007 R. Doemer

14

Scope Rules: Example

```
#include <stdio.h>
int square(int a);
int add_y(int x);
int x = 5,
     y = 7;
int square(int a)
{
    int s;
    s = a * a;
    return s;
}
int add_y(int x)
{
    int s;
    s = x + y;
    return s;
}
int main(void)
{
    int z;
    z = square(x);
    z = add_y(z);
    printf("%d\n", z);
    return 0;
}
```

*Local variables
are independent!*

(unless their scopes are nested)

Scope of local variable
s

Scope of local variable
s

Scope of local variable
z

EECS10: Computational Methods in ECE, Lecture 15

(c) 2007 R. Doemer

15

Scope Rules: Example

```
#include <stdio.h>
int square(int a);
int add_y(int x);
int x = 5,
     y = 7;
int square(int a)
{
    int s;
    s = a * a;
    return s;
}
int add_y(int x)
{
    int s;
    s = x + y;
    return s;
}
int main(void)
{
    int z;
    z = square(x);
    z = add_y(z);
    printf("%d\n", z);
    return 0;
}
```

Scope of parameter
x

EECS10: Computational Methods in ECE, Lecture 15

(c) 2007 R. Doemer

16

Scope Rules: Example

```
#include <stdio.h>
int square(int a);
int add_y(int x);
int x = 5,
    y = 7;
int square(int a)
{
    int s;
    s = a * a;
    return s;
}
int add_y(int x)
{
    int s;
    s = x + y;
    return s;
}
int main(void)
{
    int z;
    z = square(x);
    z = add_y(z);
    printf("%d\n", z);
    return 0;
}
```

Shadowing!

In nested scopes,
inner scope takes precedence!

Scope of global variable

x

Scope of parameter

x

EECS10: Computational Methods in ECE, Lecture 15

(c) 2007 R. Doemer

17

Debugging

- Source-level Debugger **gdb**
 - Basic **gdb** commands
 - **run**
 - starts the execution of the program in the debugger
 - **break *function_name***
 - inserts a breakpoint at ***function_name***
 - program execution will stop at the breakpoint
 - **list *line_numbers***
 - lists the current or specified ***line_numbers***
 - **print *variable_name***
 - prints the current value of the variable ***variable_name***
 - **next**
 - executes the next statement (one statement at a time)
 - **quit**
 - exits the debugger (and terminates the program)
 - **help**
 - provides helpful details on debugger commands

EECS10: Computational Methods in ECE, Lecture 15

(c) 2007 R. Doemer

18

Debugging

- Source-level Debugger **gdb** (continued)
 - Additional **gdb** commands
 - **step**
 - steps into a function call
 - **finish**
 - continues execution until the current function is finished
 - **where**
 - shows where in the function call hierarchy you are
 - prints a *back trace* of current *stack frames*
 - **up**
 - steps up one stack frame (up into the caller)
 - **down**
 - steps down one stack frame (down into the callee)
 - **info locals**
 - lists the local variables in the current function (current stack frame)
 - **info scope *function_name***
 - lists the variables in scope of the *function_name*

Scope Rules: Example

- Program example: **Scope.c** (part 1/2)

```
/* Scope.c: example demonstrating scope rules */
/* author: Rainer Doemer */
/* modifications: */
/* 10/30/04 RD initial version */

#include <stdio.h>

int square(int a); /* global function declarations */
int add_y(int x);

int x = 5,           /* global variables */
    y = 7;

int square(int a)   /* global function definition */
{
    int s;           /* local variable */

    s = a * a;
    return s;
}
...
```

Scope Rules: Example

- Program example: **Scope.c** (part 2/2)

```
...
int add_y(int x)          /* global function definition */
{
    int s;                /* local variable */
    s = x + y;
    return s;
}

int main(void)            /* main function definition */
{
    int z;                /* local variable */
    z = square(x);
    z = add_y(z);

    printf("%d, %d, %d\n", x, y, z);
    return 0;
}
/* EOF */
```

Scope Rules: Example

- Example session: **Scope.c** (part 1/3)

```
% vi Scope.c
% gcc Scope.c -o Scope -Wall -ansi -g
% Scope
5, 7, 32
% gdb Scope
GNU gdb 5.0
[...]
(gdb) break main
Breakpoint 1 at 0x1079c: file Scope.c, line 36.
(gdb) run
Starting program: /users/faculty/doemer/eecs10/Scope/Scope

Breakpoint 1, main () at Scope.c:36
36      z = square(x);
(gdb) step
square (a=5) at Scope.c:20
20      s = a * a;
(gdb) next
21      return s;
...
EE
```

Scope Rules: Example

- Example session: **scope.c** (part 2/3)

```
...
(gdb) next
22
(gdb) next
main () at Scope.c:37
37      z = add_y(z);
(gdb) step
add_y (x=25) at Scope.c:28
28      s = x + y;
(gdb) where
#0  add_y (x=25) at Scope.c:28
#1  0x107c4 in main () at Scope.c:37
(gdb) up
#1  0x107c4 in main () at Scope.c:37
37      z = add_y(z);
(gdb) down
#0  add_y (x=25) at Scope.c:28
28      s = x + y;
...
...
```

EECS10: Computational Methods in ECE, Lecture 15

(c) 2007 R. Doemer

23

Scope Rules: Example

- Example session: **scope.c** (part 3/3)

```
...
(gdb) finish
Run till exit from #0  add_y (x=25) at Scope.c:28
0x107c4 in main () at Scope.c:37
37      z = add_y(z);
Value returned is $1 = 32
(gdb) info locals
z = 25
(gdb) info scope square
Scope for square:
Symbol a is an argument at stack/frame offset 68, length 4.
Symbol s is a local variable at frame offset -20, length 4.
(gdb) info scope add_y
Scope for add_y:
Symbol x is an argument at stack/frame offset 68, length 4.
Symbol s is a local variable at frame offset -20, length 4.
(gdb) quit
%
```

EECS10: Computational Methods in ECE, Lecture 15

(c) 2007 R. Doemer

24