

EECS 10: Homework 3

Prof. Rainer Doemer

October 12, 2007

Due Monday, October 22 at 12:00pm

1. Part 1: Compute the approximate value of e^x (10 points)

Write a C program to calculate the value of e to the power of x . The result can be approximated using an infinite sum:

$$e^x = 1 + x + \frac{1}{2!}x^2 + \frac{1}{3!}x^3 + \dots + \frac{1}{n!}x^n + \dots$$

Your program must use only the basic operations such as addition, subtraction, multiplication and division. Also, please follow the same programming style as discussed in Lecture 5 for the cosine function (i.e. do not use any loops in your program).

The goal is to compute the value of e^x such that the result has a precision of 3 decimal places. For example, if the value of $e^{1.5} = 4.481689\dots$, then your program should output $e^{1.5} = 4.481xxxx$ (where “x” is any digit).

In your program, you should use as many terms from the above formula as necessary to just achieve the above mentioned precision for the three values given below.

$$e^{0.3} = 1.349xxx$$

$$e^{0.5} = 1.648xxx$$

$$e^{1.0} = 2.718xxx$$

When executed, your program should look like this:

```
Please enter the real value x: 1.0
e to the power of x is approximately 2.718xxx
```

You should submit your program code as file **e.c**, a text file **e.txt** briefly explaining how you designed your program, and a typescript **e.script** which shows that you compile your program and run it using the values 0.3, 0.5 and 1.0 as inputs.

2. Part 2: Calculate the weekday for any date (30 points)

Zeller's congruence (source: http://en.wikipedia.org/wiki/Zeller%27s_congruence) is an algorithm devised by Christian Zeller to calculate the day of the week for any calendar date. For today's Gregorian calendar, Zeller's congruence is

$$w = \left(d + \left\lfloor \frac{(m+1) * 26}{10} \right\rfloor + K + \left\lfloor \frac{K}{4} \right\rfloor + \left\lfloor \frac{J}{4} \right\rfloor + 5J \right) \bmod 7, \text{ where}$$

w is the day of the week (0 means Saturday, 1 means Sunday, 2 means Monday, ...),

d is the day of the month ($1 \leq d \leq 31$),

m is the month ($1 \leq m \leq 12$), and

y is the year of the calendar date ($1582 \leq y \leq 2099$).

Further, the above equation distinguishes

J as the century (that is, $J = \left\lfloor \frac{y}{100} \right\rfloor$) and

K as the year of the century (that is, $K = y \bmod 100$).

Finally, there is an exception in Zeller's congruence for the months of January and February which need to be counted as month 13 and 14, respectively, of the previous year. Thus, if $m=1$ or $m=2$, then we need to add 12 months to the value of m , and subtract 1 year from y before we feed the values into the above equation.

Your weekday calculation program should contain the following sections:

1. Data input: Let the user enter a valid calendar date in the following format:

Please enter a calendar date:

Day **d = 22**

Month **m = 10**

Year **y = 2007**

2. Data preprocessing: Handle the exception for the months of January and February if $m < 3$ then add 12 to m and subtract 1 from y

3. Computation: Use Zeller's congruence

Hint: The floor function $\lfloor x \rfloor$ is implicit in any integer division.

That is, if a and b are both integer variables, then $\left\lfloor \frac{a}{b} \right\rfloor = a/b$.

4. Output the numerical result: Use the following format

For the date 10/22/2007, the day of the week is 2.

You should submit your program code as file `weekday.c`, a text file `weekday.txt` briefly explaining how you designed your program, and a typescript `weekday.script` which shows that you compile your program and run it. Use the following dates as inputs:

10/22/2007 (the deadline for this assignment),

01/01/2008 (next New Year's day), and

10/04/1965 (the first day of classes at UCI).

3. Bonus Problem [5 Points]

The program output of Part 2 uses a numerical identifier (0 – 6) to represent the computed weekday. In this bonus problem, we will extend our program so that it prints the result as a regular text string, i.e. Saturday, Sunday, Monday, ..., or Friday. Thus, given the date listed above, the program should output:

```
For the date 10/22/2007, the day of the week is 2.  
This is a Monday.
```

Hint: You may use seven if statements to create this output.

To submit, use the same files as in Part 2, i.e. `weekday.c`, `weekday.txt`, and `weekday.script`.

4. Submission

Submission for the files will be similar to last week's assignment. The only difference is that you need to create a directory called `hw3/`. Put all the files for assignment 3 in that directory and run the `/ecelib/bin/turnin` command to submit your homework.