

EECS 10: Computational Methods in Electrical and Computer Engineering

Lecture 21

Rainer Dömer

doemer@uci.edu

The Henry Samueli School of Engineering
Electrical Engineering and Computer Science
University of California, Irvine

Lecture 21: Overview

- **Basic Computer Architecture**
 - Computer components
- **Binary Data Representation**
 - Bits, bytes, and words
 - Memory sizes
 - Memory format
 - Number systems
 - Memory segmentation

Basic Computer Architecture

- Essential Computer Components
 - Central Processing Unit (CPU)
 - e.g. Intel Pentium, Motorola PowerPC, Sun SPARC, ...
 - Random Access Memory (RAM)
 - storage for program and data, read and write access
 - Read Only Memory (ROM)
 - fixed storage for basic input/output system (BIOS)
 - I/O Units
 - Input/output units connecting to peripherals

The diagram illustrates the basic computer architecture. A 'Clock' block on the left provides a signal to the 'CPU'. The 'CPU' is connected to 'RAM', 'ROM', and 'I/O' blocks. A 'Data Bus' is shown as a horizontal line with arrows pointing to the CPU, RAM, and ROM. An 'Address Bus' is shown as a horizontal line with arrows pointing from the CPU to the RAM and ROM. 'I/O Busses' are shown as two horizontal lines with arrows pointing to and from the I/O block.

EECS10: Computational Methods in ECE, Lecture 21 (c) 2010 R. Doemer 3

Binary Data Representation

- Programs and data in a computer are represented in binary format
 - 1 *bit* (binary digit), 2 possible values
 - 0 (false, “no”, power off, “empty”, ...)
 - 1 (true, “yes”, power on, “solid”, ...)
 - 1 *byte* = 8 bits ($2^8 = 256$ values)
 - in C, type `char` equals one byte*
 - 1 *word* = 4 bytes* ($2^{32} = 4294967296$ values)
 - in C, type `int` equals one word
- Memory size is measured in Bytes
 - 1 KB = 1024 byte = 1 “kilo byte”
 - 1 MB = 1024*1024 byte = 1 “mega byte”
 - 1 GB = 1024*1024*1024 byte = 1 “giga byte”

(*architecture dependent!)

EECS10: Computational Methods in ECE, Lecture 21 (c) 2010 R. Doemer 4

Binary Data Representation

- Memory is composed of addressable bytes
 - Example:
 - 1 KB of memory
 - What is the value at address 7?

7

7 6 5 4 3 2 1 0

$$= 0 \cdot 2^7 + 1 \cdot 2^6 + 0 \cdot 2^5 + 0 \cdot 2^4 + 1 \cdot 2^3 + 1 \cdot 2^2 + 0 \cdot 2^1 + 1 \cdot 2^0$$

$$= 0 \cdot 128 + 1 \cdot 64 + 0 \cdot 32 + 0 \cdot 16 + 1 \cdot 8 + 1 \cdot 4 + 0 \cdot 2 + 1 \cdot 1$$

$$= 64 + 8 + 4 + 1$$

$$= 77$$

0
1
2
3
4
5
6
7
8
9
10
11

...

1020
1021
1022
1023

EECS10: Computational Methods in ECE, Lecture 21
(c) 2010 R. Doemer
5

Binary Data Representation

- Number Systems
 - DEC: Decimal numbers
 - Base 10, digits 0, 1, 2, 3, ..., 9
 - e.g. $157 = 1 \cdot 10^2 + 5 \cdot 10^1 + 7 \cdot 10^0$
 - BIN: Binary numbers
 - Base 2, digits 0, 1
 - e.g. $10011101_2 = 1 \cdot 2^7 + 0 \cdot 2^6 + \dots + 1 \cdot 2^0$
 - OCT: Octal numbers
 - Base 8, digits 0, 1, 2, 3, ..., 7
 - e.g. $235_8 = 2 \cdot 8^2 + 3 \cdot 8^1 + 5 \cdot 8^0$
 - HEX: Hexadecimal numbers
 - Base 16, digits 0, 1, 2, 3, ..., 9, A, B, C, ..., F
 - e.g. $9D_{16} = 9 \cdot 16^1 + 13 \cdot 16^0$

EECS10: Computational Methods in ECE, Lecture 21
(c) 2010 R. Doemer
6

Binary Data Representation

- Number Systems

DEC	BIN	OCT	HEX
0	0000	0	0
1	0001	1	1
2	0010	2	2
3	0011	3	3
4	0100	4	4
5	0101	5	5
6	0110	6	6
7	0111	7	7
8	1000	10	8
9	1001	11	9
10	1010	12	A
11	1011	13	B
12	1100	14	C
13	1101	15	D
14	1110	16	E
15	1111	17	F

EECS10: Computational Methods in ECE, Lecture 21

(c) 2010 R. Doemer

7

Binary Data Representation

- Number Systems (signed vs. unsigned)

SDEC	UDEC	BIN	OCT	HEX
0	0	0000	0	0
1	1	0001	1	1
2	2	0010	2	2
3	3	0011	3	3
4	4	0100	4	4
5	5	0101	5	5
6	6	0110	6	6
7	7	0111	7	7
-8	8	1000	10	8
-7	9	1001	11	9
-6	10	1010	12	A
-5	11	1011	13	B
-4	12	1100	14	C
-3	13	1101	15	D
-2	14	1110	16	E
-1	15	1111	17	F

EECS10: Computational Methods in ECE, Lecture 21

(c) 2010 R. Doemer

8

Binary Data Representation

- Number Systems
 - Signed representation: *two's complement*
 - to obtain the negative of any number in binary representation, ...
 - ... invert all bits,
 - ... and add 1
 - Example: 4-bit two's complement

SDEC	UDEC	BIN	OCT	HEX
...
7	7	0111	7	7
-8	8	1000	10	8
-7	9	1001	11	9
...

EECS10: Computational Methods in ECE, Lecture 21 (c) 2010 R. Doemer 9

Binary Data Representation

- Memory Segmentation
 - typical (virtual) memory layout on processor with 4-byte words and 1 GB of memory
 - Stack
 - grows and shrinks dynamically
 - function call hierarchy
 - stack frames with local variables
 - Heap
 - “free” storage
 - dynamic allocation by the user
 - Data segment
 - global (and static) variables
 - Program segment
 - stores binary program code
 - Reserved area for operating system


bfff fffc

0

EECS10: Computational Methods in ECE, Lecture 21 (c) 2010 R. Doemer 10

Binary Data Representation

- Memory Segmentation
 - typical (virtual) memory layout on processor with 4-byte words and 1 GB of memory
- Memory errors
 - *Out of memory*
 - Stack and heap collide
 - *Segmentation fault*
 - access outside allocated segments
 - e.g. access to segment reserved for OS
 - *Bus error*
 - mis-aligned word access
 - e.g. word access to an address that is not divisible by 4



EECS10: Computational Methods in ECE, Lecture 21

(c) 2010 R. Doemer

11