

EECS 10: Computational Methods in Electrical and Computer Engineering

Lecture 8

Rainer Dömer

doemer@uci.edu

The Henry Samueli School of Engineering
Electrical Engineering and Computer Science
University of California, Irvine

Lecture 8: Overview

- Keywords in C
- Counters
 - Augmented Assignment Operators
 - Increment and Decrement Operators
- Repetition Statements
 - `while` loop
- Counter-controlled repetition
 - Example `Average.c`
- Sentinel-controlled repetition
 - Example `Average2.c`

Keywords in C

- List of keywords in ANSI-C

- auto - double - int - struct
- break - else - long - switch
- case - enum - register - typedef
- char - extern - return - union
- const - float - short - unsigned
- continue - for - signed - void
- default - goto - sizeof - volatile
- do - if - static - while

- These keywords are reserved!
- These cannot be used as identifiers.
- More keywords are reserved for C++

Augmented Assignment Operators

- Assignment operator: =
 - evaluates right-hand side
 - assigns result to left-hand side
- Augmented assignment operators: +=, *=, ...
 - evaluates right-hand side as temporary result
 - applies operation to left-hand side and temporary result
 - assigns result of operation to left-hand side
- Example: Counter
 - `int c = 0; /* counter starting from 0 */`
 - `c = c + 1; /* counting by regular assignment */`
 - `c += 1; /* counting by augmented assignment */`
- Augmented assignment operators:
 - +=, -=, *=, /=, %=, <<=, >>=, |=, &&=

Increment and Decrement Operators

- Counting in steps of one
 - increment (add 1)
 - decrement (subtract 1)
- C provides special operators
 - increment operator: ++
 - `count++` post-increment (`count += 1`)
 - `++count` pre-increment (`count += 1`)
 - decrement operator: --
 - `count--` post-decrement (`count -= 1`)
 - `--count` pre-increment (`count -= 1`)
 - *pre-* increment/decrement
 - value returned is the incremented/decremented (new) value
 - *post-* increment/decrement
 - value returned is the original (old) value


EECS10: Computational Methods in ECE, Lecture 8

(c) 2010 R. Doemer

5

Repetition Statements

- Repetition (aka. iteration, loop)
 - repeated execution of a block of statements
 - counter-controlled
 - counter determines number of repetitions (often predefined at compile time)
 - sentinel-controlled
 - sentinel condition determines number of repetitions (usually determined at run time)
- Control flow chart



EECS10: Computational Methods in ECE, Lecture 8

(c) 2010 R. Doemer

6

Repetition Statements

- **while** loop
 - Control flow statement for repetition (iteration)
 - Repeats execution depending on a specified condition
 - Example:


```
int product = 2;
while (product < 1000)
  { product *= 2; }
printf("Product is %d", product);
```
 - Syntax: **while** construct consists of
 - keyword `while`
 - condition expression evaluated to true or false
 - body statement block
 - Semantics: the body is repeatedly executed as long as the condition evaluates to true
 - the condition is evaluated at the *beginning* of each loop

EECS10: Computational Methods in ECE, Lecture 8

(c) 2010 R. Doemer

7

Example Program

- Average of values: **Average.c** (part 1/3)

```
/* Average.c: compute the average of a set of numbers */
/*
/* author: Rainer Doemer
/*
/* modifications:
/* 10/10/04 RD initial version
*/

#include <stdio.h>

/* main function */

int main(void)
{
  /* variable definitions */
  int counter;
  double value;
  double total;
  double average;
  ...
}
```

EECS10: Computational Methods in ECE, Lecture 8

(c) 2010 R. Doemer

8

Example Program

- Average of values: `Average.c` (part 2/3)

```
...  
  
/* input and computation section */  
counter = 1;  
total = 0.0;  
while (counter <= 10)  
{ printf("Please enter value %d: ", counter);  
  scanf("%lf", &value);  
  total += value;  
  counter++;  
} /* elihw */  
  
/* computation section */  
average = total / 10.0;  
  
...
```

Example Program

- Average of values: `Average.c` (part 3/3)

```
...  
  
/* output section */  
printf("The average is %f.\n", average);  
  
/* exit */  
return 0;  
} /* end of main */  
  
/* EOF */
```

Example Program

- Example session: `Average.c`

```
% vi Average.c
% gcc Average.c -o Average -Wall -ansi
% Average
Please enter value 1: 23
Please enter value 2: 25
Please enter value 3: 17
Please enter value 4: 18.6
Please enter value 5: 50.8
Please enter value 6: 33.3
Please enter value 7: 12
Please enter value 8: 42
Please enter value 9: 42.2
Please enter value 10: 34
The average is 29.790000.
%
```

Repetition Statements

- Explicit control flow in loops
 - **break** statement
 - exits the innermost loop
 - **continue** statement
 - jump back to the beginning of the innermost loop

• Example:

```
int i = 0;
int s = 0;
while (1) /* "endless" loop */
{
    i++;
    if (i > 10)
        { break; } /* exit the loop */
    if (i % 2 == 1)
        { continue; } /* next iteration */
    s += i;
} /* elihw */
printf("%d", s);
```

Example Program

- Average of values: `Average2.c` (part 1/3)

```

/* Average2.c: compute the average of a set of numbers */
/*
/* author: Rainer Doemer */
/*
/* modifications: */
/* 10/10/04 RD sentinel controlled loop */
/* 10/10/04 RD initial version */

#include <stdio.h>

/* main function */
int main(void)
{
    /* variable definitions */
    int counter;
    double value;
    double total;
    double average;
    ...

```

EECS10: Computational Methods in ECE, Lecture 8

(c) 2010 R. Doemer

13

Example Program

- Average of values: `Average2.c` (part 2/3)

```

...

/* input and computation section */
counter = 0;
total = 0.0;
while (1)
{ printf("Please enter a value (or -1 to quit): ");
  scanf("%lf", &value);
  if (value == -1.0)
  { break;
    } /* fi */
  total += value;
  counter++;
} /* elihw */

...

```

EECS10: Computational Methods in ECE, Lecture 8

(c) 2010 R. Doemer

14

Example Program

- Average of values: `Average2.c` (part 3/3)

```

...

/* computation and output section */
printf("%d values entered.\n", counter);
if (counter >= 1)
    { average = total / (double)counter;
      printf("The average is %f.\n", average);
    } /* fi */

/* exit */
return 0;
} /* end of main */

/* EOF */

```

Example Program

- Example session: `Average2.c`

```

% vi Average2.c
% gcc Average2.c -o Average2 -Wall -ansi
% Average2
Please enter a value (or -1 to quit): 2
Please enter a value (or -1 to quit): 3
Please enter a value (or -1 to quit): 4
Please enter a value (or -1 to quit): 5
Please enter a value (or -1 to quit): -1
4 values entered.
The average is 3.500000.
% Average2
Please enter a value (or -1 to quit): -1
0 values entered.
%

```