Embedded Systems Modeling and Design ECPS 203 Fall 2017



Assignment 4

Posted: October 25, 2017

Due: November 1, 2017 at 6pm

Topic: From single image to video stream processing

1. Setup:

With this assignment, we resume the modeling of our application example, the Canny Edge Detector. This week, we will convert the application from single image processing to video stream handling. More specifically, we will process a sequence of images extracted from a stream of video frames.

We will use the same Linux account and the same remote servers as for the previous assignments. Start by creating a new working directory, so that you can properly submit your deliverables in the end.

mkdir hw4 cd hw4

Instead of the previous golf cart image, we will from now on use the video that we captured by flying a drone over the Engineering Hall building at UCI. As before, we want to convert the original video frames into edge images using the Canny algorithm.





Our captured video is available in a shared directory on the server. To save disk space, do not copy the data into your account, but create a symbolic link to it, as follows:

ln -s ~ecps203/public/DroneFootage DroneFootage

Note that we do not have a working video player available on the EECS Linux servers (due to copyright reasons). However, you can easily download the DroneFootage/DJI_0003.MOV movie file to your local laptop and play it there.

2. Prepare a set of video frames suitable for use in a test bench

In order to use the captured video stream in a test bench of a SystemC model, we need to extract a sample set of frames and convert those to grey-scale images that our Canny application can process.

Step 1: Extract individual video frames from the movie file

In order to store image frames, let's first create a directory video for storing these frames:

```
mkdir video
cd video
ln -s ../DroneFootage/DJI_0003.MOV
```

Our captured video is a few minutes long, but for our design and development in SystemC, we only need a few representative frames for processing in our test bench. To keep later timing calculations simple, we will extract 30 frames from the stream, representing 1 second of real-time video at 30 frames per second (FPS).

We have installed the ffmpeg software package on the Linux servers which is a powerful video processing tool. To get an overview, browse the ffmpeg documentation which is available online here:

```
https://www.ffmpeg.org/ffmpeg.html
```

A typical call to extract video frames looks like this:

```
/opt/pkg/ffmpeg/bin/ffmpeg -ss starttime -t length -i video.mov
-r ratio frame%03d.png
```

Select suitable parameters for *starttime*, *length*, and *ratio* in order to extract 30 "pretty" video frames of your choice from our drone movie.

As a result, you should store 30 image files named "Engineering001.png" through "Engineering030.png" in your video directory. You can view these images easily with the Linux eog tool.

Step 2: Convert the color frames to grey-scale images in PGM format

Since our Canny application can only read PGM input images, we need to convert the PNG frames appropriately. Here, you can use the pngtopnm and ppmtopgm Linux tools. You can run these either separately or simply in a shell pipeline fashion. Please refer to their manual pages for detailed instructions.

As a result, you should create 30 additional image files named "Engineering001.pgm" through "Engineering030.pgm" in your video directory. Again, you can view these images easily with the Linux eog tool.

3. Convert your Canny application to process a stream of video frames

With the video frames prepared, we can now remodel the Canny application from Assignment 2 to process these images and convert them into corresponding edge images.

Step 1: Recode your Canny C++ model to process a sequence of video frames

As starting point, you can use your own C++ model which you have created in the previous Assignment 2. Alternatively, you may start from the provided solution for Assignment 2 which you can copy as follows:

```
cd hw4
cp ~ecps203/public/CannyA2 ref.cpp Canny.cpp
```

To process the 30 frames, put a loop into the main function around the load, canny, and save function calls and adjust the code so that the names used match the frame names prepared in your video directory. For example, the first image read should be "video/Engineering001.pgm" and the corresponding edge image should be stored as file "video/Engineering001_edges.pgm".

Note that you will also need to change the image size from formerly 320x240 pixels to the higher resolution of 2704x1520 pixels produced by the drone camera.

The higher image resolution naturally leads to higher memory usage of our application. Specifically, the array variables holding the image data (which we introduced in Assignment 2) grow large. Note that many of those variables are local variables which get allocated on the stack. At the same time, the stack size of a process in the Linux environment is typically limited. If so, your application will "crash" with a segmentation fault or similar memory error.

To avoid stack overflow, you can adjust the stack space allocation in your Linux shell. This configuration depends on the shell you are using, which you can identify with the following command:

```
echo $SHELL
```

If you use the csh or tcsh shell, then adjust your stack size as follows:

```
limit stacksize 128 megabytes
```

On the other hand, if you use the sh or bash shell, then set your stack size like this:

```
ulimit -s 128000
```

With this large stack allocation in place, your application model should run without memory problems. Run the Canny application on the prepared input images and validate the generated edge images in the video directory with the eog tool.

4. Submission:

For this assignment, submit the following deliverables:

Canny.cpp Canny.txt

Again, the text file should briefly mention whether or not your efforts were successful and what (if any) problems you encountered. Please be brief!

Note that you don't need to submit your image files. We only need your application source file and corresponding text file for grading. To submit these files, change into the parent directory of your hw4 directory and run the ~ecps203/bin/turnin.sh script.

As before, remember that you can use the turnin-script to submit your work at any time before the deadline, *but not after!* We recommend to submit early and even incomplete work, in order to avoid missing the hard deadline.

To double-check that your submitted files have been received, you can run the ~ecps203/bin/listfiles.py script.

For any technical questions, please use the course message board.

--

Rainer Doemer (EH3217, x4-9007, doemer@uci.edu)