

EECS 10: Computational Methods in Electrical and Computer Engineering

Lecture 14

Rainer Dömer

doemer@uci.edu

The Henry Samueli School of Engineering
Electrical Engineering and Computer Science
University of California, Irvine

Lecture 14: Overview

- Recursion
 - Concept of recursion
 - Recursion vs. iteration
 - Examples
 - Factorial function: `Factorial.c`
 - Fibonacci series: `Fibonacci.c`
- Data Structures
 - Structures, unions, enumerators
 - Type definitions
 - Example
 - Student records: `students.c`

Recursion

- Introduction
 - Recursion is often an alternative to *Iteration*
 - Recursion is a very simple concept, yet very powerful
 - Recursion is present in nature
 - Trees have branches, which have branches, which have branches, ... which have leaves.
 - Recursion is traversal of hierarchy
 - Traverse (climb) a tree to the top:
 - start at the root
 - at a leaf, stop
 - at a branch, *traverse* one branch
 - Traverse a file system on a computer
 - start at the current directory
 - at a file, process the file
 - at a directory, *traverse* the directory

Recursion

- Recursive Function
 - Function that calls itself
 - ... directly, or
 - ... indirectly
- Concept of Recursion
 - Trivial *base case*
 - Return value defined for simple case
 - Example: `if (param==0) {return 1;}`
 - *Recursion step*
 - Reduce the problem towards the base case
 - Make a recursive function call
 - Example: `if (param>0) {return ...fct(param-1);}`
- Termination of Recursion
 - Converging of recursive calls to the base case
 - Recursive call must be “simpler” than current call

```
int f(...)  
{ ...  
  f(...);  
  ...  
}
```

```
int a(...)  
{ ...  
  b(...);  
  ...  
}  
int b(...)  
{ ...  
  a(...);  
  ...  
}
```

Recursion

- Example: Factorial function $n!$
 - The factorial of a non-negative integer is
 - $n! = n * (n-1) * (n-2) * (n-3) * \dots * 1$
 - This can be written as
 - $n! = n * ((n-1) * ((n-2) * ((n-3) * (\dots * 1))))$
 - *Recursive definition:*
 - $n=1: 1! = 1$ (base case)
 - $n > 1: n! = n * (n-1)!$ (recursion step)

- Example computation:

$$\begin{aligned}
 5! &= 5 * 4! \\
 &= 5 * (4 * 3!) \\
 &= 5 * (4 * (3 * 2!)) \\
 &= 5 * (4 * (3 * (2 * 1!))) \\
 &= 5 * (4 * (3 * (2 * 1))) \\
 &= 5 * (4 * (3 * 2)) \\
 &= 5 * 24 \\
 &= 120
 \end{aligned}$$

EECS10: Computational Methods in ECE, Lecture 14

(c) 2019 R. Doemer

5

Recursion

- Program example: **Factorial.c** (part 1/2)

```

/* Factorial.c: example demonstrating recursion */
/* author: Rainer Doemer */ 
/* modifications: */ 
/* 11/14/04 RD initial version */ 

#include <stdio.h>

/* function definition */
long factorial(long n)
{
    if (n == 1)           /* base case */
    {
        return 1;
    } /* fi */
    else                  /* recursion step */
    {
        return n * factorial(n-1);
    } /* esle */
} /* end of factorial */
...

```

EECS10: Computational Methods in ECE, Lecture 14

(c) 2019 R. Doemer

6

Recursion

- Program example: **Factorial.c** (part 2/2)

```
...
int main(void)
{
    /* variable definitions */
    long int n, f;

    /* input section */
    printf("Please enter value n: ");
    scanf("%ld", &n);

    /* computation section */
    f = factorial(n);

    /* output section */
    printf("The factorial of %ld is %ld.\n", n, f);

    /* exit */
    return 0;
} /* end of main */

/* EOF */
```

Recursion

- Example session: **Factorial.c**

```
% vi Factorial.c
% gcc Factorial.c -o Factorial -Wall -ansi
% ./Factorial
Please enter value n: 1
The factorial of 1 is 1.
% ./Factorial
Please enter value n: 2
The factorial of 2 is 2.
% ./Factorial
Please enter value n: 3
The factorial of 3 is 6.
% ./Factorial
Please enter value n: 5
The factorial of 5 is 120.
% ./Factorial
Please enter value n: 10
The factorial of 10 is 3628800.
%
```

Recursion vs. Iteration

- Example: Factorial function $n!$
 - The factorial of a non-negative integer is
 - $n! = n * (n-1) * (n-2) * (n-3) * \dots * 1$
 - This can be written as
 - $n! = n * ((n-1) * ((n-2) * ((n-3) * (\dots * 1))))$
 - *Recursive definition:*
 - $n=1: 1! = 1$ (base case)
 - $n > 1: n! = n * (n-1)!$ (recursion step)
 - *Iterative implementation:*
 - Compute n products in a loop
 - $n! = n * (n-1) * (n-2) * (n-3) * \dots * 1$
 - ```
p = n;
for (f=n-1; f>=1; f--)
{ p = p * f; }
```

EECS10: Computational Methods in ECE, Lecture 14

(c) 2019 R. Doemer

9

## Recursion vs. Iteration

- Program example: **Factorial2.c** (part 1/2)

```
/* Factorial2.c: example demonstrating iteration */
/* author: Rainer Doemer */
/* modifications: */
/* 11/14/04 RD initial version (based on Factorial.c) */

#include <stdio.h>

/* function definition */
long factorial(long n)
{
 long product, factor;

 product = n;
 for(factor = n-1; factor >= 1; factor--)
 { product *= factor;
 } /* rof */
 return product;
} /* end of factorial */
...
```

EECS10: Computational Methods in ECE, Lecture 14

(c) 2019 R. Doemer

10

## Recursion vs. Iteration

- Program example: **Factorial2.c** (part 2/2)

```
...
int main(void)
{
 /* variable definitions */
 long int n, f;

 /* input section */
 printf("Please enter value n: ");
 scanf("%ld", &n);

 /* computation section */
 f = factorial(n);

 /* output section */
 printf("The factorial of %ld is %ld.\n", n, f);

 /* exit */
 return 0;
} /* end of main */

/* EOF */
```

## Recursion vs. Iteration

- Example session: **Factorial2.c**

```
% cp Factorial.c Factorial2.c
% vi Factorial2.c
% gcc Factorial2.c -o Factorial2 -Wall -ansi
% ./Factorial2
Please enter value n: 1
The factorial of 1 is 1.
% ./Factorial2
Please enter value n: 2
The factorial of 2 is 2.
% ./Factorial2
Please enter value n: 3
The factorial of 3 is 6.
% ./Factorial2
Please enter value n: 5
The factorial of 5 is 120.
% ./Factorial2
Please enter value n: 10
The factorial of 10 is 3628800.
%
```

# Recursion

- Example 2: Fibonacci series
  - Sequence of integers
    - 0, 1, 1, 2, 3, 5, 8, 13, 21, 34, 55, 89, 144, 233, 377, 610, 987, ...
  - Mathematical properties
    - The first two numbers are 0 and 1
    - Every subsequent Fibonacci number is the sum of the previous two Fibonacci numbers
  - Ratio of successive Fibonacci numbers is ...
    - ... converging to constant value 1.618...
    - ... called *Golden Ratio* or *Golden Mean*
  - Recursive definition:
    - Base case:  $\text{fibonacci}(0) = 0$   
 $\text{fibonacci}(1) = 1$
    - Recursion step:  $\text{fibonacci}(n) = \text{fibonacci}(n-1) + \text{fibonacci}(n-2)$

# Recursion

- Program example: **Fibonacci.c** (part 1/2)

```
/* Fibonacci.c: example demonstrating recursion */
/* author: Rainer Doemer */
/* modifications: */
/* 11/14/04 RD initial version */

#include <stdio.h>

/* function definition */
long fibonacci(long n)
{
 if (n <= 1) /* base case */
 {
 return n;
 } /* fi */
 else /* recursion step */
 {
 return fibonacci(n-1) + fibonacci(n-2);
 } /* esle */
} /* end of fibonacci */

/* main function */
...
```

## Recursion

- Program example: **Fibonacci.c** (part 2/2)

```
...
int main(void)
{
 /* variable definitions */
 long int n, f;

 /* input section */
 printf("Please enter value n: ");
 scanf("%ld", &n);

 /* computation section */
 f = fibonacci(n);

 /* output section */
 printf("The %ld-th Fibonacci number is %ld.\n", n, f);

 /* exit */
 return 0;
} /* end of main */

/* EOF */
```

## Recursion

- Example session: **Fibonacci.c**

```
% cp Factorial.c Fibonacci.c
% vi Fibonacci.c
% gcc Fibonacci.c -o Fibonacci -Wall -ansi
% ./Fibonacci
Please enter value n: 1
The 1-th Fibonacci number is 1.
% ./Fibonacci
Please enter value n: 10
The 10-th Fibonacci number is 55.
% ./Fibonacci
Please enter value n: 20
The 20-th Fibonacci number is 6765.
% ./Fibonacci
Please enter value n: 30
The 30-th Fibonacci number is 832040.
% ./Fibonacci
Please enter value n: 40
The 40-th Fibonacci number is 102334155.
%
```

## Data Structures

- Structures (aka. records): **struct**
  - User-defined, composite data type
    - Type is a composition of (different) sub-types
  - Fixed set of members
    - Names and types of members are fixed at structure definition
  - Member access by name
    - Member-access operator: ***structure\_name.member\_name***
- Example:

```
struct S { int i; float f; } s1, s2;

s1.i = 42; /* access to members */
s1.f = 3.1415;
s2 = s1; /* assignment */
s1.i = s1.i + 2*s2.i;
```

## Data Structures

- Structure Declaration
  - Declaration of a user-defined data type
- Structure Definition
  - Definition of structure members and their type
- Structure Instantiation and Initialization
  - Definition of a variable of structure type
  - Initializer list defines initial values of members
- Example:

```
struct Student; /* declaration */

struct Student /* definition */
{ int ID; /* members */
 char Name[40];
 char Grade;
};

struct Student Jane = /* instantiation */
{1001, "Jane Doe", 'A'}; /* initialization */
```

## Data Structures

- Structure Access
  - Members are accessed by their name
  - Member-access operator .
- Example:

```
struct Student
{
 int ID;
 char Name[40];
 char Grade;
};

struct Student Jane =
{1001, "Jane Doe", 'A'};

void PrintStudent(struct Student s)
{
 printf("ID: %d\n", s.ID);
 printf("Name: %s\n", s.Name);
 printf("Grade: %c\n", s.Grade);
}
```

| Jane  |            |
|-------|------------|
| ID    | 1001       |
| Name  | "Jane Doe" |
| Grade | 'A'        |

```
ID: 1001
Name: Jane Doe
Grade: A
```

## Data Structures

- Unions: **union**
  - User-defined, composite data type
    - Type is a composition of (different) sub-types
  - Fixed set of *mutually exclusive* members
    - Names and types of members are fixed at union definition
  - Member access by name
    - Member-access operator: `union_name.member_name`
  - *Only one member may be used at a time!*
    - *All members share the same location in memory!*
- Example:

```
union U { int i; float f; } u1, u2;

u1.i = 42; /* access to members */
u2.f = 3.1415;
u1.f = u2.f; /* destroys u1.i! */
```

## Data Structures

- Union Declaration
  - Declaration of a user-defined data type
- Union Definition
  - Definition of union members and their type
- Union Instantiation and Initialization
  - Definition of a variable of union type
  - Single initializer defines value of *first* member
- Example:

```
union HeightOfTriangle; /* declaration */
union HeightOfTriangle /* definition */
{ int Height; /* members */
 int LengthOfSideA;
 float AngleBeta;
};


union HeightOfTriangle H /* instantiation */
= { 42 }; /* initialization */
```

## Data Structures

- Union Access
  - Members are accessed by their name
  - Member-access operator .
- Example:

```
union HeightOfTriangle
{ int Height;
 int SideA;
 float Beta;
};

union HeightOfTriangle t1, t2, t3
= { 42 };
```




## Data Structures

- Union Access
  - Members are accessed by their name
  - Member-access operator .
- Example:

```
union HeightOfTriangle
{
 int Height;
 int SideA;
 float Beta;
};

union HeightOfTriangle t1, t2, t3
= { 42 };

void SetHeight(void)
{
 t1.Height = 10;
 t2.SideA = t1.Height / 2;
 t3.Beta = 90.0;
}
```



## Data Structures

- Enumerators: **enum**
  - User-defined data type
    - Members are an enumeration of integral constants
  - Fixed set of members
    - Names and values of members are fixed at enumerator definition
  - Members are constants
    - Member values cannot be changed after definition
- Example:

```
enum E { red, yellow, green };
enum E LightNS, LightEW;

LightEW = green; /* assignment */
if (LightNS == green) /* comparison */
{ LightEW = red; }
```

## Data Structures

- Enumerator Declaration
  - Declaration of a user-defined data type
- Enumerator Definition
  - Definition of enumerator members and their value
- Enumerator Instantiation and Initialization
  - Definition of a variable of enumerator type
  - Initializer should be one member of the enumerator
- Example:

```
enum Weekday; /* declaration */
enum Weekday /* definition */
{ Monday, Tuesday, /* members */
 Wednesday, Thursday,
 Friday, Saturday, Sunday
};

enum Weekday Today /* instantiation */
= Tuesday; /* initialization */
```

## Data Structures

- Enumerator Values
  - Enumerators are represented as integer constants
  - By default, enumerator values start at 0 and are incremented by 1 for each following member
- Example:

Today

Tuesday

Day: 1

```
enum Weekday
{
 Monday,
 Tuesday,
 Wednesday,
 Thursday,
 Friday,
 Saturday,
 Sunday
};

enum Weekday Today
= Tuesday;

void PrintWeekday(
 enum Weekday d)
{
 printf("Day: %d\n", d);
}
```

## Data Structures

- Enumerator Values
  - Enumerators are represented as integer constants
  - By default, enumerator values start at 0 and are incremented by 1 for each following member
  - Specific enumerator values may be defined by the user
- Example:

Today

Tuesday

Day: 2

```
enum Weekday
{ Monday = 1,
 Tuesday,
 Wednesday,
 Thursday,
 Friday,
 Saturday,
 Sunday
};

enum Weekday Today
= Tuesday;

void PrintWeekday(
 enum Weekday d)
{
 printf("Day: %d\n", d);
}
```

## Data Structures

- Enumerator Values
  - Enumerators are represented as integer constants
  - By default, enumerator values start at 0 and are incremented by 1 for each following member
  - Specific enumerator values may be defined by the user
- Example:

Today

Tuesday

Day: 3

```
enum Weekday
{ Monday = 2,
 Tuesday,
 Wednesday,
 Thursday,
 Friday,
 Saturday,
 Sunday = 1
};

enum Weekday Today
= Tuesday;

void PrintWeekday(
 enum Weekday d)
{
 printf("Day: %d\n", d);
}
```

# Data Structures

- Type definitions: **typedef**
  - A **typedef** can be defined as an alias type for another type
  - A **typedef** definition follows the same rules as a variable definition
  - Type definitions are usually used to abbreviate access to user-defined types
- Examples:

```
typedef signed long int MyInteger;
MyInteger i1 = 42;

typedef enum Weekday Day;
Day Today = Tuesday;

typedef struct Student Scholar;
Scholar Jane, John;
```

# Data Structures

- Program example: **Students.c** (part 1/6)

```
/* Students.c: simple array of student records */
/* author: Rainer Doemer */
/* modifications: */
/* 08/28/13 RD initial version */

#include <stdio.h>
#include <stdlib.h>

/* constants */
#define SLEN 40
#define MAX 100

/* data structures */

struct Student
{
 int ID;
 char Name[SLEN];
 int Score;
};
typedef struct Student STUDENT;

STUDENT Record[MAX];
int N = 0;
...
```

## Data Structures

- Program example: **Students.c** (part 2/6)

```
...
/* function declarations */
STUDENT EnterStudent(void);
void PrintStudent(STUDENT s);
char LetterGrade(int Score);
void InsertStudent(STUDENT s);

/* function definitions */

STUDENT EnterStudent(void)
{
 STUDENT s;

 printf("Enter student ID: ");
 scanf("%d", &s.ID);
 printf("Enter student name: ");
 scanf("%39s", &s.Name[0]);
 printf("Enter student score: ");
 scanf("%d", &s.Score);
 return s;
}

...
```

## Data Structures

- Program example: **Students.c** (part 3/6)

```
...
void PrintStudent(STUDENT s)
{
 printf("ID %3d: %39s, Score %3d% = %c\n",
 s.ID, s.Name, s.Score, LetterGrade(s.Score));
}

char LetterGrade(int Score)
{
 switch(Score/10)
 {
 case 10:
 case 9: return 'A';
 case 8: return 'B';
 case 7: return 'C';
 case 6: return 'D';
 case 5: case 4: case 3: case 2: case 1:
 case 0: return 'F';
 default: break;
 } /* hctiws */
 return '-';
}
```

## Data Structures

- Program example: **Students.c** (part 4/6)

```
...
void InsertStudent(STUDENT s)
{
 int i, j;

 for(i=0; i<N; i++)
 {
 if (s.ID < Record[i].ID)
 { break; }
 }
 for(j=N; j>i; j--)
 {
 Record[j] = Record[j-1];
 }
 Record[i] = s;
 N++;
}
...
```

## Data Structures

- Program example: **Students.c** (part 5/6)

```
...
int main(void)
{
 int Choice, i;

 while(1)
 { printf("Student records: %d\n", N);
 printf("1. Enter new student\n");
 printf("2. Print student table\n");
 printf("3. Quit\n");
 printf("Choice: ");
 scanf("%d", &Choice);
 switch(Choice)
 { case 1:
 { if (N < MAX)
 { InsertStudent(EnterStudent());
 }
 break;
 }
 ...
}
```

## Data Structures

- Program example: **Students.c** (part 6/6)

```
...
 case 2:
 {
 for(i=0; i<N; i++)
 {
 PrintStudent(Record[i]);
 }
 break;
 }
 case 3:
 {
 exit(0);
 }
 default:
 {
 break;
 }
 } /* hctiws */
} /* elihw */
return 0;
} /* end of main */

/* EOF */
```

## Data Structures

- Example session: **Students.c** (part 1/3)

```
% vi Students.c
% gcc Students.c -o Students -Wall -ansi
% ./Students
Student records: 0
1. Enter new student
2. Print student table
3. Quit
Choice: 1
Enter student ID: 1879
Enter student name: Albert_Einstein
Enter student score: 100
Student records: 1
1. Enter new student
2. Print student table
3. Quit
Choice: 2
ID 1879: Albert_Einstein , Score 100% = A
...
```

## Data Structures

- Example session: **Students.c** (part 2/3)

```
...
Student records: 1
1. Enter new student
2. Print student table
3. Quit
Choice: 1
Enter student ID: 1642
Enter student name: Isaac_Newton
Enter student score: 100
Student records: 2
1. Enter new student
2. Print student table
3. Quit
Choice: 2
ID 1642: Isaac_Newton , Score 100% = A
ID 1879: Albert_Einstein , Score 100% = A
...
...
```

## Data Structures

- Example session: **Students.c** (part 3/3)

```
[...]
Choice: 1
Enter student ID: 1623
Enter student name: Blaise_Pascal
Enter student score: 100
Student records: 3
1. Enter new student
2. Print student table
3. Quit
Choice: 2
ID 1623: Blaise_Pascal , Score 100% = A
ID 1642: Isaac_Newton , Score 100% = A
ID 1879: Albert_Einstein , Score 100% = A
Student records: 3
1. Enter new student
2. Print student table
3. Quit
Choice: 3
%
```